DayTech LED

5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

LED PUCK LIGHT · PRODUCT SPECIFICATION

3W Magnetic-Trim Puck – CCT Tunable

PART NO. **LED-NL404 SERIES**

3-in-1 CCT · 210 lm · 24V DC · CRI 90 · 120° · Magnetic changeable trim · Recessed or surface



SHOWN WITH WHITE TRIM

3 W POWER	**210 lm** LUMEN OUTPUT
24 V DC INPUT VOLTAGE	**3-IN-1** 3000K / 4000K / 6000K
90 CRI COLOUR RENDERING	**ø80 mm** DIAMETER · 21 MM HIGH

MAGNETIC TRIM · **3-IN-1 CCT** · **DIMMABLE** · **24V DC** · **6 TRIM FINISHES**

cETLus LISTED

PRODUCT OVERVIEW

A 3W puck with a **magnetic, changeable trim** and **3-in-1 colour temperature**: a dip switch selects **3000K, 4000K or 6000K** on site. Delivers **210 lumens** at **CRI 90** with a 120° beam on **24V DC**. Dimmable; installs **recessed** in a ø60 mm cutout or **surface mounted**. Trims in **silver, white, black, brushed nickel, gold or chrome**.

TRIM & HOUSING



TRIM
Magnetic, changeable

CCT
3K / 4K / 6K dip switch

CUTOUT
ø60 mm

SIZE
ø80 × 21 mm (H)


SPECIFICATIONS

SERIES	**LED-NL404 (6 models)**
POWER	3 W
INPUT VOLTAGE	24 V DC
LUMINOUS FLUX	210 lm
COLOUR TEMP.	CCT tunable 3000K / 4000K / 6000K (dip switch)
CRI	90
BEAM ANGLE	120°
DIMMING	Dimmable
IP RATING	IP21
SIZE	ø80 mm × 21 mm (H)
CUTOUT	ø60 mm
TRIM	Magnetic, changeable
TRIM FINISH	Silver · White · Black · Brushed nickel · Gold · Chrome
INSTALLATION	Recessed or surface mount
CERTIFICATION	cETLus listed

DIMENSIONS

Dimensions in mm

SURFACE MOUNTING · RECESSED MOUNTING



RECESSED CUTOUT ø60 MM

Specifications subject to change without notice.

DayTech LED


5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

Options & Ordering

PART NO. **LED-NL404 SERIES**

6 models: 1 colour temperature × 6 body colours, 24V DC only. Tick each part number you need and enter a quantity.

TRIM FINISH



Silver
no suffix



White
-WHT



Black
-BLK



Brushed Nickel
-BN



Golden
-GLD



Chrome
-CHR

PART NUMBER KEY

LED-NL404	+	3 CCT	+	-24V	+	none / -WHT / -BLK / -BN / -GLD / -CHR
SERIES		WATTS + COLOUR TEMP.		24V DC		FINISH

EXAMPLE
LED-NL404-3CCT-24V-BN

ORDERING INFORMATION

COLOUR TEMP. · 24V DC	SILVER no suffix	WHITE -WHT	BLACK -BLK	BRUSHED NICKEL -BN	GOLDEN -GLD	CHROME -CHR
CCT Tunable 3000K + 4000K + 6000K · dip	LED-NL404-3CCT-24V QTY	LED-NL404-3CCT-24V-WHT QTY	LED-NL404-3CCT-24V-BLK QTY	LED-NL404-3CCT-24V-BN QTY	LED-NL404-3CCT-24V-GLD QTY	LED-NL404-3CCT-24V-CHR QTY

All models 3W · 210 lm · 3K/4K/6K dip switch · CRI 90 · 120° · magnetic trim · cETLus

TOTAL PUCKS

ORDER DETAILS

COMPANY

CONTACT / PHONE

PO #

PROJECT

DATE REQUIRED

NOTES

POWER REQUIREMENT

Runs on **24V DC** only. Size the power supply for the number of fixtures (**3 W each**, allow ~20% headroom). Power supply ordered separately.

Specifications subject to change without notice.