DayTech LED

5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

LED PUCK LIGHT · PRODUCT SPECIFICATION

3W Ultra-Thin Puck – CCT Tunable

PART NO. **LED-NL405 SERIES**

7 mm thin · 210 lm · 24V DC · 3000K / 4000K dip switch · CRI 90 · 120° · Flush or surface mount



WHITE, BLACK & BRUSHED NICKEL TRIMS

7 mm ULTRA-THIN PROFILE	**3 W** POWER
210 lm LUMEN OUTPUT	**24 V DC** INPUT VOLTAGE
3K/4K DIP-SWITCH CCT	**ø70 mm** DIAMETER

7 MM ULTRA-THIN · **CCT SELECTABLE** · **MAGNETIC TRIM** · **DIMMABLE** · **24V DC**

cETLus LISTED

PRODUCT OVERVIEW

An **ultra-thin 7 mm** puck for shallow cabinets and shelving where depth is tight. A dip switch selects **3000K or 4000K**, and the **trim is changeable**. Delivers **210 lumens** at **CRI 90** with a 120° beam on **24V DC**. Dimmable; **flush or surface mount**. Trims in **white, black or brushed nickel**.

FRONT VIEW



PROFILE
7 mm

CCT
3000K / 4000K

MOUNT
Flush or surface

SIZE
ø70 × 7 mm (H)


SPECIFICATIONS

SERIES	**LED-NL405 (3 models)**
POWER	3 W
INPUT VOLTAGE	24 V DC
LUMINOUS FLUX	210 lm
COLOUR TEMP.	CCT tunable 3000K / 4000K (dip switch)
CRI	90
BEAM ANGLE	120°
DIMMING	Dimmable
IP RATING	IP21
SIZE	ø70 mm × 7 mm (H)
TRIM	Changeable
TRIM FINISH	White · Black · Brushed nickel
INSTALLATION	Flush or surface mount
CERTIFICATION	cETLus listed


DIMENSIONS

Dimensions in mm

FRONT



PROFILE



7 MM ULTRA-THIN PROFILE

Specifications subject to change without notice.

DayTech LED


5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

Options & Ordering

PART NO. **LED-NL405 SERIES**

3 models: 1 colour temperature × 3 body colours, 24V DC only. Tick each part number you need and enter a quantity.

TRIM FINISH



WHITE

-WHT

Part number suffix



BLACK

-BLK

Part number suffix



BRUSHED NICKEL

-BN

Part number suffix

PART NUMBER KEY

LED-NL405	+	3 CCT	+	-24V	+	-WHT / -BLK / -BN
SERIES		WATTS + COLOUR TEMP.		24V DC		FINISH

EXAMPLE
LED-NL405-3CCT-24V-BLK

ORDERING INFORMATION

COLOUR TEMP. · 24V DC	WHITE -WHT	BLACK -BLK	BRUSHED NICKEL -BN
CCT Tunable 3000K + 4000K · dip switch	LED-NL405-3CCT-24V-WHT QTY	LED-NL405-3CCT-24V-BLK QTY	LED-NL405-3CCT-24V-BN QTY

All models 3W · 210 lm · 3000K/4000K dip switch · CRI 90 · 7 mm thin · cETLus

TOTAL PUCKS

ORDER DETAILS

COMPANY | CONTACT / PHONE | PO #

PROJECT | DATE REQUIRED | NOTES

POWER REQUIREMENT

Runs on **24V DC** only. Size the power supply for the number of fixtures (**3 W each**, allow ~20% headroom). Power supply ordered separately.

Specifications subject to change without notice.