DayTech LED

5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

LED STEP LIGHT · PRODUCT SPECIFICATION

1W Square LED Step Light

PART NO. **LEDSTEP-SQ-NL602 SERIES**

1W · 90 lm · 24V DC · 45° beam · PWM dimmable · Recessed · ø40 mm cutout



SHOWN IN SILVER FINISH

ALSO IN





1 W POWER	**90 lm** LUMEN OUTPUT
24 V DC INPUT VOLTAGE	**45°** BEAM ANGLE
55×55 mm SQUARE FACE · 30 MM DEEP	**ø40 mm** CUTOUT

STEP & WALL · **PWM DIMMABLE** · **24V DC** · **5 COLOUR TEMPS** · **3 FINISHES**

cETLus LISTED

PRODUCT OVERVIEW

A **square 1W LED step light** that washes light down across stairs, corridors and walkways. Delivers **90 lumens** with a 45° beam on **24V DC**, and is **PWM dimmable**. Installs **recessed** in a ø40 mm cutout. Five colour temperatures from **2700K to 6000K**, in **silver, white or black**.

IN USE



BEAM
45°, downward

FACE
55×55

CUTOUT
ø40 mm

DEPTH
30 mm


SPECIFICATIONS

SERIES	**LEDSTEP-SQ-NL602 (15 models)**
POWER	1 W
INPUT VOLTAGE	24 V DC
LUMINOUS FLUX	90 lm
COLOUR TEMP.	EW 2700K · WW 3000K · NW 4000K · DW 5000K · W 6000K
BEAM ANGLE	45°
DIMMING	PWM dimmable
IP RATING	IP21
SIZE	55×55 × 30 mm (H)
CUTOUT	ø40 mm
FINISH	Silver · White · Black
INSTALLATION	Recessed (wall / step)
CERTIFICATION	cETLus listed


DIMENSIONS

Dimensions in mm

SIDE



FRONT



WALL CUTOUT ø40 MM

Specifications subject to change without notice.

DayTech LED

5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

Options & Ordering

PART NO. **LEDSTEP-SQ-NL602 SERIES**

15 models: 5 colour temperatures × 3 body colours, 24V DC only. Tick each part number you need and enter a quantity.


FINISH



SILVER

STANDARD

No suffix



WHITE

-WHT

Part number suffix



BLACK

-BLK

Part number suffix

PART NUMBER KEY

LEDSTEP-SQ-NL602	+	1 EW / WW / NW / DW / W	+	-24V	+	none / -WHT / -BLK
SERIES		WATTS + COLOUR TEMP.		24V DC		FINISH

EXAMPLE
LEDSTEP-SQ-NL602-1NW-24V-WHT

ORDERING INFORMATION

COLOUR TEMP. · 24V DC	SILVER no suffix	WHITE -WHT	BLACK -BLK
EW Extra Warm White 2700K	LEDSTEP-SQ-NL602-1EW-24V QTY	LEDSTEP-SQ-NL602-1EW-24V-WHT QTY	LEDSTEP-SQ-NL602-1EW-24V-BLK QTY
WW Warm White 3000K	LEDSTEP-SQ-NL602-1WW-24V QTY	LEDSTEP-SQ-NL602-1WW-24V-WHT QTY	LEDSTEP-SQ-NL602-1WW-24V-BLK QTY
NW Neutral White 4000K	LEDSTEP-SQ-NL602-1NW-24V QTY	LEDSTEP-SQ-NL602-1NW-24V-WHT QTY	LEDSTEP-SQ-NL602-1NW-24V-BLK QTY
DW Daylight White 5000K	LEDSTEP-SQ-NL602-1DW-24V QTY	LEDSTEP-SQ-NL602-1DW-24V-WHT QTY	LEDSTEP-SQ-NL602-1DW-24V-BLK QTY
W Cool White 6000K	LEDSTEP-SQ-NL602-1W-24V QTY	LEDSTEP-SQ-NL602-1W-24V-WHT QTY	LEDSTEP-SQ-NL602-1W-24V-BLK QTY

All models 1W · 90 lm · 45° · PWM dimmable · IP21 · ø40 mm cutout · cETLus

TOTAL STEP LIGHTS

ORDER DETAILS

COMPANY

CONTACT / PHONE

PO #

PROJECT

DATE REQUIRED

NOTES

POWER REQUIREMENT

Runs on **24V DC** only. Size the power supply for the number of fixtures (**1 W each**, allow ~20% headroom). Power supply ordered separately.

Specifications subject to change without notice.