DayTech LED

5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

LED ALUMINUM PROFILE · PRODUCT SPECIFICATION

1622 Slim U-Profile

PART NO. **NL-AP-1622-2M**



SPECIFICATIONS


APPLICATION	Surface or pendant
MATERIAL	6063-T5, double-anodized
STANDARD LENGTH	2 m
PROFILE FINISH	Black (std) · Silver/White 3 wk
PC COVER	Frosted or Milky
LED STRIP	10 – 14 mm, flexible or rigid
DIMENSIONS	16 × 22 mm (W × H)
MOUNTING	Brackets or steel cable

PRODUCT OVERVIEW

The 1622 is a **slim, deep U-profile** in aviation-grade 6063-T5 aluminum, double-anodized, for flexible or rigid LED strip **10 – 14 mm** wide. A weather- and UV-resistant, flame-retardant PC cover protects the LEDs, and it mounts to surfaces with brackets or **suspends** on steel cables.

CROSS SECTION

Dimensions in mm



COMPONENTS & ACCESSORIES



Aluminum Profile
NL-AP-1622-2M
2 m · black, silver, white



PC Cover
Included
Frosted or milky



End Caps
NL-AP-1622-C
Polypropylene QTY



Mounting Clips
NL-AP-C1622
Brackets QTY



Suspension Kit
NL-AP-R60-HK
Steel cable QTY

MOUNTING OPTIONS



PENDANT
Suspended on steel cables



SURFACE
Wall or ceiling, mounting brackets

SURFACE OR PENDANT MOUNTING

ORDERING INFORMATION

PART NUMBER — Includes PC cover

NL-AP-1622-2M

FINISH: ☐ ■ Black · ☐ Silver · ☐ White (BLACK STD)
COVER: ☐ Frosted · ☐ Milky

LENGTH: ☐ 2 m std TOTAL ____ M
QTY ____ PO # ____
PROJECT ____

Specifications subject to change without notice.