DayTech LED

5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

LED ALUMINUM PROFILE · PRODUCT SPECIFICATION

2515 Recessed Profile

PART NO. **NL-AP-2515-3M**



SPECIFICATIONS


APPLICATION	Recessed ceiling / drywall
MATERIAL	AL6063-T5 anodized aluminum
STANDARD LENGTH	3 m silver/black · 2 m white
PROFILE FINISH	Silver, Black · White (3 wk)
PC COVER	Frosted, Milky or Black
LED STRIP	1 line, up to 12 mm
DIMENSIONS	17.4 × 15.7 mm (W × H)
ACCESSORIES	NL-AP-2515-C, NL-AP-C6

PRODUCT OVERVIEW

The 2515 is a **recessed, ceiling-mounted** profile that houses LED strip lighting and provides a uniform, linear light. It mounts into a surface such as drywall and sits **flush**, giving a clean, finished appearance.

CROSS SECTION


Dimensions in mm



COMPONENTS



Aluminum Profile
3 m silver/black · 2 m white



End Caps
NL-AP-2515-C QTY




Mounting Clips
NL-AP-C6 QTY



INCLUDED

PC Diffuser Cover
Frosted, Milky or Black

RECESSED · CUT A GROOVE 18 MM WIDE × 14 MM DEEP



INSTALLATION GUIDE

ORDERING INFORMATION

PART NUMBER — Includes PC cover

NL-AP-2515-3M

FINISH ☐ Silver ☐ Black ☐ White

COVER ☐ Frosted ☐ Milky ☐ Black

LENGTH 3 m std TOTAL _____ M

QTY _____ PO # _____

PROJECT _____