
DayTech LED

5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

LED ALUMINUM PROFILE · PRODUCT SPECIFICATION

9818 Extra-Wide Drywall Profile

PART NO. **NL-AP-9818-2M**



SPECIFICATIONS


APPLICATION	Recessed, mud-in drywall
MATERIAL	6063-T5 aluminum alloy
STANDARD LENGTH	2 m
PROFILE FINISH	Silver
COVER	Frosted PC (70–90%), included
INTERNAL WIDTH	47 mm (LED strip up to 47 mm)
DIMENSIONS	98 × 15.5 mm (flange W × H)
IP RATING	IP20 · –30 °C to +100 °C

PRODUCT OVERVIEW


The 9818 is an **extra-wide, recessed** aluminum profile that is plastered into drywall or ceilings for **bold, seamless lines of light**. It holds up to two LED strips (47 mm total) behind a frosted diffuser, and once mudded in, no aluminum remains visible.

CROSS SECTION

Dimensions in mm



COMPONENTS & ACCESSORIES



Aluminum Profile

NL-AP-9818-2M

2 m · silver



Frosted Cover

Included

Frosted PC diffuser



End Caps

NL-AP-9818-C QTY

Closes profile ends



Connectors

Inquire

L, T and straight joins



APPLICATION · SEAMLESS WALL & CEILING LINES

ORDERING INFORMATION

PART NUMBER — Includes frosted cover

NL-AP-9818-2M

FINISH ☐ Silver (Only finish) | COVER Frosted (Included)

LENGTH ☐ 2 m std | TOTAL _____ M

QTY _____ | PO # _____

PROJECT _____

Specifications subject to change without notice.

DayTech LED

5250 Satellite Drive, Unit 7, Mississauga ON L4W 5G5
Tel 905-617-0298
www.daytechled.com

LED ALUMINUM PROFILE · TECHNICAL DATA

Technical Specs & Installation

PART NO. **NL-AP-9818-2M**


PRODUCT DETAILS


Made from high-quality 6063-T5 aluminum, this extra-wide extrusion holds up to two flexible or rigid LED strips, up to 47 mm wide in total. LEDs sit behind a polycarbonate diffuser that is UV-stable, weather-resistant and flame-retardant. Polypropylene end caps keep dust and debris off the strip to protect light output. Once plastered in, the profile disappears into the wall or ceiling, leaving a clean line of light with no visible aluminum.

TECHNICAL SPECIFICATIONS

INGRESS PROTECTION	IP20 (standard)	HEAT STABILITY	Under 100 °C
AVAILABLE LENGTH	2 m (cut to size)	FLAMMABILITY	V2 fire rating (PC cover)
BODY MATERIAL	Aluminum, 6063-T5	UL94 RATING	UL94 V2
COVER MATERIAL	Polycarbonate (PC)	UV STABILITY	Ageing resistance > 3 years
END CAP MATERIAL	Polypropylene	TOLERANCE	±0.5 mm
LIGHT TRANSMITTANCE	Frosted cover, 70–90%	ANODIZING	Ecru / sand-blast oxidation
OPERATING TEMPERATURE	–30 °C to +100 °C	SPECIFIC HEAT	880 J/(kg · °C)

INSTALLATION · MUD-IN DRYWALL





STEPS

1. Cut the drywall opening to suit the profile.
2. Fix the profile with a suitable mounting adhesive or screws.
3. Apply a thin layer of adhesive to the flange and embed drywall mesh.
4. Cover with filler, then sand and paint once dry.
5. Install the LED strip, fit the frosted cover and end caps (NL-AP-9818-C).

Specifications subject to change without notice.